

In the Claims:

Claims 1-6 (cancelled).

7. (Currently Amended) A method of determining a location of a print media within an electrophotographic imaging device where the print media is moved therethrough while an image is generated and transferred to the print media, the method comprising:

applying a bias voltage to a fuser to charge the fuser ~~to have a fuser bias voltage~~, the ~~fuser~~ bias voltage being affected by the print media contacting the fuser;

fusing the image to the print media with the fuser;

measuring the ~~fuser~~ bias voltage; and

determining whether the print media is in the fuser based on the measured ~~fuser~~ bias voltage.

8. (Original) The method as set forth in claim 7 wherein the applying includes applying the bias voltage at a substantially constant value.

9. (Currently Amended) The method as set forth in claim 7 wherein the determining includes generating a status signal that indicates the print media is in the fuser when the measured ~~fuser~~ bias voltage differs from the applied bias voltage.

10. (Original) The method as set forth in claim 9 wherein, if the print media jams within the imaging device, displaying an error message indicating a location of the print media based on the status signal.

11. (Currently Amended) The method as set forth in claim 7 wherein the determining includes comparing the measured ~~fuser~~ bias voltage to the applied bias voltage.

12. (Currently Amended) The method as set forth in claim 11 further including setting a threshold value and generating a status signal when a difference between the measured ~~fuser~~ bias voltage and the applied bias voltage is greater than ~~that~~ the threshold value.

13. (Currently Amended) The method as set forth in claim 7 wherein the measuring includes detecting a change in the measured ~~fuser~~ bias voltage where the change indicates whether the print media is in the fuser.

14. (Original) The method as set forth in claim 7 wherein the measuring includes measuring the bias voltage across the fuser.

15. An image fusing system comprising:

a fuser including:

a fuser roller having a heating element; and

a pressure roller in pressure engagement with the fuser roller where a print media passes therebetween, the fuser and pressure rollers fusing an image onto the print media through heat and pressure;

a voltage circuit for applying a bias voltage to the fuser where the bias voltage reduces toner particles from being attracted to the fuser; and

a fuser sensor circuit for detecting the bias voltage of the fuser and indicating that the print media is within the fuser when the detected bias voltage changes.

16. (Original) The image fusing system as set forth in claim 15 wherein the fuser is an on-demand fuser.

17. (Original) The image fusing system as set forth in claim 15 wherein the fuser sensor circuit is connected to the voltage circuit and detects the bias voltage across the fuser.

18. (Original) The image fusing system as set forth in claim 15 wherein the fuser sensor circuit detects the bias voltage directly from the fuser.

19. (Original) The image fusing system as set forth in claim 15 further including a charging brush connected to the voltage circuit and being in contact with the fuser roller where the charging brush charges the fuser roller according to the bias voltage.

- 20. The image fusing system as set forth in claim 15 wherein the fuser sensor circuit includes a comparator logic that compares the detected bias voltage to the bias voltage applied and sets a status signal based on a difference therebetween.

21. (Original) The image fusing system as set forth in claim 15 wherein the fuser sensor circuit includes means for detecting a change of the bias voltage on the fuser.

22. (Previously Presented) The method as set forth in claim 7 wherein applying the bias voltage is to reduce toner particles from being attracted to the fuser.

In making the above disclaimer, Hewlett-Packard does not disclaim the terminal part of any patent granted on the instant application that would extend to the expiration date of the full statutory term as defined in 35 U.S.C. §§154 and 173 of the prior patent, as presently shortened by any terminal disclaimer, in the event that it later: (a) expires for failure to pay a maintenance fee, (b) is held unenforceable, (c) is found invalid by a court of competent jurisdiction, (d) is statutorily disclaimed in whole or terminally disclaimed under 37 CFR §1.321, (e) has all claims canceled by a reexamination certificate, (f) is reissued, or (g) is in any manner terminated prior to the expiration of its full statutory term as presently shortened by any terminal disclaimer.


Pursuant to 37 C.F.R. §1.20(d), the terminal disclaimer fee is \$110.00. Please charge this amount to Deposit Account 08-2025 to cover the cost of the terminal disclaimer. The Commissioner is hereby authorized to charge any additional fees to Deposit Account 08-2025, specifically identifying Attorney Docket No. 10014654-3.

The undersigned is an attorney of record.

Conclusion

For the reasons stated above, claims 7-22 are now in condition for allowance. An early allowance of all claims is earnestly solicited.

Respectfully submitted,



PETAR KRAGULJAC (Reg. No. 38,520)

(216) 363-4162

04/07/2004 SHAWASS1 00000019 082025 10612078
01 FC1814 110.00 DA